



DF

DISINFECTION

- removes more than 99% of bacteria from the water

WATER FLOWS

up to 0.5 GPM

PERFORMANCE

- water volume: up to 3,000 gallons of use
- contains high quality coconut shell GAC that reduces:
 - odor and organics

CERTIFICATIONS

Quantum Disinfection™ is:

- a NSF Certified Component to NSF/ANSI 42 for material requirements only (Certificate #: C0292640-01)
- tested by IAPMO to NSF/ANSI 61 (Certificate #: 23033)
- Certified MOH - China (Certificate #: 2015KF2513)



No chemicals. No power. No pathogens

MAIN USE

- post RO for bacteria reduction (*E. coli*)

Application	Point-of-Use
Power Requirements	None
Main Use	Water Disinfection
Flow rates	0.5 GPM 2 L/min
Unit Dimensions	10 x 2 inch 25 x 5 cm
Min Operating Pressure	25 psi 1.7 bar
Max Operating Pressure	125 psi 8.6 bar
Expected Life	3,000 gallons 11,100 liters
Operating Temperature	41 - 100 °F 5 - 38 °C
Disinfection Capacity	> 99%
Inlet/Outlet Connection Size	QC - 3/8 inch
Replaceable Cartridge	Yes



Contact



info@aquaoxfilters.com



(803) 709-7378



www.aquaoxfilters.com



720 Old Clemson Rd Suite L
Columbia, SC 29229

