

POINT OF USE

DISINFECTION FILTER

Quantum Disinfection™

Under-Sink Carbon + DF Water Filter



- removes more than 99% of bacteria from the water

WATER FLOWS

1 GPM

PERFORMANCE

- water volume: more than 15,000 gallons of use

contains high quality coconut shell GAC that reduces:sediment, Chlorine, odor and organics

CERTIFICATIONS

Quantum Disinfection™ is:

- a NSF Certified Component to NSF/ANSI 42 for material requirements only (Certificate #: C0292640-01)

- tested by IAPMO to NSF/ANSI 61 (Certificate #: 23033)

- Certified MOH - China (Certificate #: 2015KF2513)

No chemicals. No power. No pathogens

MULTIPLE USES

under-the-counter unit
marine and recreational vehicles
water coolers
beverage/OCS

Application	Point-of-Use
Power Requirements	None
Main Use	- Water Disinfection - Taste & Odor Removal
Flow rates	1 GPM 3.7 L/min
Unit Dimensions	12 x 3 inch 31 x 8 cm
Min Operating Pressure	25 psi 1.7 bar
Max Operating Pressure	125 psi 8.6 bar
Expected Life	> 15,000 gallons > 56,500 liters
Operating Temperature	41 - 100 °F 5 - 38 °C
Disinfection Capacity	> 99%
Inlet/Outlet Connection Size	QC - 3/8 inch
Replaceable Cartridge	Yes

Contact



info@aquaoxfilters.com



(803) 369-6956



www.aquaoxwaterfilters.com



720 Old Clemson Rd Suite L Columbia, SC 29229

