



DISINFECTION - removes more than 99% of bacteria from the water

WATER FLOWS

up to 24 GPM (12 GPM each)

PERFORMANCE

- water volume: up to 200,000 gallons of use

contains high quality coconut shell GAC that reduces:odor and organics

CERTIFICATIONS

Quantum Disinfection™ is:

- a NSF Certified <u>Component</u> to NSF/ANSI 42 for <u>material requirements only</u> (Certificate #: C0292640-01)

- tested by IAPMO to NSF/ANSI 61 (Certificate #: 23033)

- Certified MOH - China (Certificate #: 2015KF2513)

No chemicals. No power. No pathogens

DISINFECTION FILTER

DISINFECTION FILTER

MAIN USE

- post RO for bacteria reduction (E. coli)

Application	Whole House
Power Requirements	None
Main Use	Water Disinfection
Flow rates	24 GPM 90 L/min
Per Unit Dimensions	10 x 2 inch 25 x 5 cm
Min Operating Pressure	25 psi 1.7 bar
Max Operating Pressure	125 psi 8.6 bar
Expected Life	200,000 gallons
Operating Temperature	41 - 100 °F 5 - 38 °C
Disinfection Capacity	> 99%
Inlet/Outlet Connection Size	QC - 3/8 inch
Replaceable Cartridge	Yes

Contact



info@aquaoxfilters.com



(803) 709-7378



www.aquaoxfilters.com



720 Old Clemson Rd Suite L Columbia, SC 29229



